



Belt Dressing BD-3

Belt Slip Preventer

Aerosol 420 ml



Features

- Applied to any materials including plain belt, V belt, rubber or fabric.
- Increase friction coefficient of belt to prevent idling.
- Preventing polishing to prevent dust or foreign substances.
- Increasing belt cohesion to transmit force evenly.
- Belt noise prevention and life extension.

Applications

- Industrial Drives
- Compressor
- Automobile
- Farm Machinery
- Marine Equip.
- Power Tools
- Conveyer

How to use

- Spray Method : Spray it to the surface and inside of belt while belt operates.
- Brush Method : Brush it uniformly on the inside of belt to prevent belt idling.

Cautions

- Remove dust or dirt off applied surface to apply it. Use brush or sand paper to remove rust or scale and apply it.
- Do not spray directly onto the face or food. Do not inhale or intake.
- Keep it out of the reach of children.
- As this is an inflammable product using high pressure gas, keep the following cautions carefully.
- 1. Do not spray directly toward open flame.
- 2. Do not use it near any heat sources such as radiators, heat registers, stoves, or other apparatus



(including amplifiers) that produce heat.

3. Do not use it in an environment where there are explosive or inflammable materials.
4. Store the product in places where the temperature does not exceed 40°C.
5. After used in enclosed areas, be sure to ventilate.
6. Do not throw into a fire.
7. After use, throw it away after checking and removal the remaining gas in the container.
8. Do not store it in enclosed area.
9. Below 5°C, injection power may be poor.

※ This information can be amended without any notice according to new knowledge and test result. If there are any questions, please contact us or the store where you purchased it.

