



LONG#2

Long-term Rust-Preventer

Aerosol 420 ml / Can, Bulk 20 l / can



Long #2 is a special long-term antirust agent. It is specially manufactured to be used in the chemical environment like hard weather condition or severe corrosion. Thick wax-type film protects equipment against moisture, acid, alkali and salinity. Excellent effects for lengthening service life, decreasing abrasion caused by corrosion, and lubrication.

Features

Powerful antirust agent (indoors : 3 years, outdoors: 2 years)

Powerful wax-type film formation.

Excellent water displacement.

Rustproofing

Thick wax-type film protects equipment against moisture, acid, alkali and salinity or their evaporation, maintaining strong antirust effects. The product maintains antirust effects for three years outdoors and two years indoors, and is used for vessels, airplanes and chemical plants.

Lubrication

Excellent anti-abrasion, antifriction and heat-resistance. Excellent permeability making it penetrate into fine cracks to show antirust and lubrication effects. Also, with excellent adhesiveness, it is not peeled easily, protecting equipment against water or sea water.

Water displacement

Low surface tension and high permeability. High water repellency and water displacement creating excellent insulation effects. Excellent electric property making it ideal for protection of electric system.

Stability

As it does not silicon except chloric solvents, it is not harmful to plastics, rubber, paint, textile, wire and plated area. Green product without using freon gas. It can be used while equipment operates. Easy-to-use aerosol product.

Uses

Equipment, tools, engine and military supplies for long-term keeping indoors and outdoors Vessels, chemical plants and airplanes under hard conditions like moisture, salinity, acid and alkali.





Automobiles, snowplow, military equipment, hoist, agricultural machinery and railway cars easily exposed to corrosion.

Outdoor electric system, irrigation facility, military transportation vehicles and their electric systems.

How to use

Aerosol Type

Shake aerosol product before use. Spray it evenly to the target objects with 20~30cm away from it.

Bulk type

Apply bulk product by using brush or roller. Or you can dip the target object to use the product.

※The film of LONG#2 is easily cleaned by NABAKEM DC-5000 or MC-2.

Cautions

Do not spray directly onto the face or food. Do not inhale or intake.

Keep it out of the reach of children.

As this is an inflammable product using high pressure gas, keep the following cautions carefully.

1. Do not spray directly toward open flame.
2. Do not use it near any heat sources such as radiators, heat registers, stoves, or other apparatus (including amplifiers) that produce heat.
3. Do not use it in an environment where there are explosive or inflammable materials.
4. Store the product in places where the temperature does not exceed 40 °C.
5. After used in enclosed areas, be sure to ventilate.
6. Do not throw into a fire.
7. After use, throw it away after checking and removal the remaining gas in the container.
8. Do not store it in enclosed area.
9. Below 5 °C, injection power may be poor.





Technical Data Sheet of LONG#2

Item	Unit	Result	Remark
Appearance	-	Semi brown liquid	Visual
Drying time	min	60 ± 30	25°C
Thickenss	μm	32.0 ± 2.0	ELCOMETER 300
Form of film	-	Waxy film	Visual
Term of antirust	Year	interior 3	-
		exterior 2	
Salt spray test	hr	>500	ASTM B 117
Spray rate (10sec)	g	15 ± 3	-
Coverage	m ² /ℓ	4.42 (30 μm)	-

※ This information can be amended without any notice according to new knowledge and test result. If there are any questions, please contact us or the store where you purchased it.

