

TAPPING SPRAY T-860

Tapping oil Spray

Aerosol 420 ml/can, 20 cans/Box



Tapping spray T-860 is an excellent tapping oil not containing chloric components. Idea for tapping, screwing, drilling and lima machining of ferrous or nonferrous metals.

Features


Easy-to-use one touch spray. Necessary amount can be sprayed to necessary applications. No loss.
Make finished surface fine. Improves dimension accuracy.
Ensuring easy treatment of cut powder. Cut powder is removed well. It prevents burned-adhesion.
Lowering high temperature in cutting. Extending tools life. Increasing tapping speed and discharge.
Applicable to all metals from special steel, stainless, titanium to aluminum.
Easy work with stainless pipe button attached.

Applications

Machine tapping and hand tapping of metals, aluminum and copper. Screwing, drilling and lima machining etc.

How to use

Connect pipe with spray nozzle to spray it.



Cautions

Remove dust or dirt off applied surface to apply it. Use brush or sand paper to remove rust or scale and apply it.
Do not spray directly onto the face or food. Do not inhale or intake.
Keep it out of the reach of children.





As this is an inflammable product using high pressure gas, keep the following cautions carefully.

1. Do not spray directly toward open flame.
2. Do not use it near any heat sources such as radiators, heat registers, stoves, or other apparatus (including amplifiers) that produce heat.
3. Do not use it in an environment where there are explosive or inflammable materials.
4. Store the product in places where the temperature does not exceed 40°C.
5. After used in enclosed areas, be sure to ventilate.
6. Do not throw into a fire.
7. After use, throw it away after checking and removal the remaining gas in the container.
8. Do not store it in enclosed area.
9. Below 5°C, injection power may be poor.

※ This information can be amended without any notice according to new knowledge and test result. If there are any questions, please contact us or the store where you purchased it.

